



ACC-RR06

Roof Rack

Yamaha G22

## Installation Instructions



Contents of ACC-RR06, Yamaha G22 Roof Rack:

- a (1 ea.) Roof Rack
- b (2 ea.) Front Mounting Brackets
- c (1 ea.) Driver Side Rear Mounting Bracket
- d (1 ea.) Passenger Side Rear Mounting Bracket
- e (2 ea.) M6 x 25mm Hex Bolts
- f (2 ea.) M6 x 40mm Hex Bolts
- g (2 ea.) M6 x 45mm Hex Bolts
- h (12 ea.) M6 Flat Washers
- i (6 ea.) M6 Lock Nuts
- j (4 ea.) M8 x 60mm Hex Bolts
- k (8 ea.) M8 Flat Washers
- l (4 ea.) M8 Lock Nuts

**Caution:** Please read through the instructions carefully. Look behind each drill location BEFORE YOU DRILL. Installer is responsible for damage (i.e. drilling into a wiring harness, battery, fuel tank etc.).

## Driver and Passenger Rear Roof Rack Mounting Brackets

1. Remove the existing mounting bolts, nuts and washers from both Rear Top Struts where they connect to the Top.
2. Install the Driver and Passenger Rear Roof Mounting Brackets using (4) M8 x 60mm Hex Bolts, (4) M8 Lock Nuts and (8) M8 Flat Washers provided in the kit. Utilize the original holes in the Rear Top Struts and Top. Do NOT fully Tighten. (Rear Passenger Bracket is shown in the photo below).



## Driver and Passenger Front Roof Rack Mounting Brackets

1. Remove the existing mounting bolts, nuts and washers from both Front Top Struts where they connect to the Top. (TOP BOLTS ONLY)
2. Install the Driver and Passenger Front Roof Mounting Brackets using (2) M6 x 45mm Hex Bolts, (2) M6 Lock Nuts and (4) M6 Flat Washers provided in the kit. Utilize the original holes in the Front Top Struts and Top. Hand tighten enough to allow adjustment of the bracket. (Front Driver Bracket is shown in the photo below).



## Roof Rack Alignment

1. Align the Roof Rack on top of the Mounting Brackets. The Rear Mounting Brackets will line up with the tabs on the rear of the Roof Rack. The square tubing of the Roof Rack will rest on the Front Mounting Brackets.
2. Once the Brackets are aligned, you will have to mark the hole locations on the underside of the square tubing of the Roof Rack for the Front Mounting Bracket holes.
3. Lower the Roof Rack to a safe, flat location and place it on a piece of cardboard to prevent from scratching the finish. Using a 1/4" drill bit, drill (2) holes through the square tubing at the marked locations.



## Roof Rack Installation

1. Lift the Roof Rack on top of the Mounting Brackets and align the mounting holes.
2. Attach the Roof Rack to the Front Mounting Brackets using (2) M6 x 40mm Hex Bolts, (4) M6 Flat Washers and (2) M6 Lock Nuts.
3. Attach the Roof Rack to the Rear Mounting Brackets using (2) M6 x 25mm Hex Bolts, (4) M6 Flat Washers and (2) M6 Lock Nuts.
4. Tighten the bolts in a diagonal pattern (i.e. Driver Front then Passenger Rear; Driver Rear then Passenger Front).

## Complete Installation

1. Fully tighten all remaining bolts.



This completes the installation of your Yamaha Roof Rack. Please enjoy safely!